

Handläggande organ	Fastställt	Utgåva	Sida
SVENSK MATERIAL- & MEKANSTANDARD, SMS	1998-04-24	2	1 (1+9)

© INNEHÅLLET I SVENSK STANDARD ÄR UPPHOVSRÄTTSLIGT SKYDDAT. SIS HAR COPYRIGHT PÅ SVENSK STANDARD. EFTERTRYCK UTAN TILLSTÅND ÄR FÖRBUDET.

## Tractors for agriculture – Operator’s field of vision

The International Standard ISO 5721:1989 has the status of a Swedish Standard. This document contains the official English version of ISO 5721:1989.

Swedish Standards corresponding to documents referred to in this Standard are listed in "Catalogue of Swedish Standards", issued by SIS. The Catalogue lists, with reference number and year of Swedish approval, International and European Standards approved as Swedish Standards as well as other Swedish Standards.

## Lantbrukstraktorer – Operatörs siktfält

Den internationella standarden ISO 5721:1989 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 5721:1989.

Motsvarigheten och aktualiteten i svensk standard till de publikationer som omnämns i denna standard framgår av "Katalog över svensk standard", som ges ut av SIS. I katalogen redovisas internationella och europeiska standarder som fastställts som svenska standarder och övriga gällande svenska standarder.

---

ICS 65.060.10

Standarder kan beställas hos SIS som även lämnar allmänna upplysningar om svensk och utländsk standard.  
Postadress: SIS, Box 6455, 113 82 STOCKHOLM  
Telefon: 08 - 610 30 00. Telefax: 08 - 30 77 57

Upplysningar om **sakinnehållet** i standarden lämnas av SMS.  
Telefon: 08 - 459 56 00. Telefax: 08 - 667 85 42  
E-post: [info@sms-standard.se](mailto:info@sms-standard.se)  
Prisgrupp M

Tryckt i juni 1998

## ISO 5721 : 1989 (E)

### Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council. They are approved in accordance with ISO procedures requiring at least 75 % approval by the member bodies voting.

International Standard ISO 5721 was prepared by Technical Committee ISO/TC 23, *Tractors and machinery for agriculture and forestry*.

This second edition cancels and replaces the first edition (ISO 5721 : 1981), of which it constitutes a revision (see the Introduction).

© ISO 1989

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization  
Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

## Introduction

In the revision of this International Standard to adopt "Seat Index Point" (SIP) in place of "Seat Reference Point" (SRP), the relationship of SIP 90 mm above and 140 mm in front of the SRP has been used. This relationship should be used when converting from SRP to SIP or vice versa.

The 1980 edition of ISO 3462, *Tractors and machinery for agriculture and forestry – Seat reference point – Method of determination* used a relationship of SIP 97 mm above and 130 mm in front of the seat reference point. In a practical comparison, however, it was found that the 90 mm vertical and the 140 mm horizontal relationship gave the most accurate conversion.

Variation from the 1980 edition of ISO 3462 is due to

- a) seat cushions not being horizontal in practice;
- b) seat cushion angle to backrest not being 90°;
- c) curvature of the backrest placing the SIP device slightly forward of the SRP device.

– Blank page –

# Tractors for agriculture – Operator's field of vision

## 1 Scope

This International Standard specifies practical and mathematical methods of determining the masking effects of obstructions on the angles of vision forward, to the rear and upwards of seated operators of tractors for agriculture.

It does not take account of detachable implements and mounted elements, for example front loaders, pallets, etc.

## 2 Normative reference

The following standard contains provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the edition indicated was valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent edition of the standard indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 5353 : 1978, *Earth-moving machinery, and tractors and machinery for agriculture and forestry – Seat index point.*

## 3 Definitions

For the purposes of this International Standard, the following definitions apply.

**3.1 field of vision** : Area which can be viewed from the seated operator's eye position.

**3.2 eye position** : Specified notional location of the operator's eye. (See clause 5.)

**3.3 semi-circle of vision to the front** : Semi-circle described about a point situated in the horizontal plane of the surface below the tractor and vertically below the eye position, such that, when facing the usual direction of motion, it is situated in front of the tractor and its limiting diameter is at right angles to the tractor longitudinal median plane. (See figure 2.)

**3.4 semi-circle of vision to the rear** : Semi-circle described about a point situated in the horizontal plane of the surface below the tractor and vertically below the eye position, such that, when facing the usual direction of motion, it is situated behind the tractor and its limiting diameter is at right angles to the tractor longitudinal median plane. (See figure 3.)

**3.5 angle of vision upwards** : Angle of vision limited downwards by a horizontal plane passing through the eye position and upwards by planes containing the rays of vision from the eye position to points of obscuration caused by vehicle components other than those which cause masking effects as defined in 3.6.

**3.6 masking effects** : Chords of the sectors of a semi-circle of vision which cannot be seen from the eye position due to structural components, for example roof pillars, exhaust pipes, etc.

## 4 Measurement accuracy

The equipment and techniques used to make the physical measurements shall be accurate to within  $\pm 2\%$ .

## 5 Eye position

The eye position shall be located 670 mm above and 10 mm in front of the seat index point when determined in accordance with ISO 5353 (see figure 1).

## 6 Practical method

NOTE – An alternative mathematical method for the determination of masking effects (see 6.4.1) is given in clause 7.

### 6.1 Test area

**6.1.1** The test area shall be capable of being darkened sufficiently to enable the light sources [see 6.2.1 b)] to cast distinct shadows or of being illuminated sufficiently to enable photographs to be taken or a sighting instrument to be used.

**6.1.2** The area shall be large enough to accommodate the semi-circles of vision set for the particular test. It should preferably be large enough to accommodate both semi-circles with a common centre point.

## ISO 5721 : 1989 (E)

**6.1.3** The test area surface shall be flat and smooth, with a maximum slope of 1 %. The deviation from flatness caused by surface irregularities shall be limited to  $\pm 25$  mm in any 1 m length on any radial line from the centre point of the semi-circle of vision. The surface shall also be firm enough to prevent measurable penetration of the ground surface by the machine.

**6.1.4** The surface should preferably be permanently marked out in 1 m squares.

**6.1.5** Where the walls of the test area constitute the vertical cylindrical surfaces [described in 6.2.1 a)], they should preferably be marked out in 1 m squares.

## 6.2 Test equipment

**6.2.1** The test equipment shall include the following:

a) Vertical walls or screens, extending from ground level to a height sufficient to detect shadows at the semi-circle of vision, for example 500 mm high, having inside surfaces which are receptive to erasable marking materials or are replaceable, and comprising:

- 1) cylindrical surfaces of inside radius equal to that of the semi-circle of vision set for the particular test, or
- 2) surfaces forming part of a semi-circle which can be progressively positioned in increments concentrically about the vertical axis through the eye position.

b) One or more of the following, which may be used singly or in combination, as desired:

- 1) two point light sources, of sufficient intensity to project clear images onto the ground and onto the vertical screens or walls, and/or
- 2) a sighting instrument having two coincident pivot axes, for example a surveyor's theodolite transit mechanism, and/or
- 3) a camera.

c) A firm support, to hold the light sources, sighting instrument and/or camera in two positions 65 mm apart, which can be

- 1) rotated through  $360^\circ$  about a vertical axis passing through the eye position, being the point midway between the light sources, and
- 2) pivoted in the vertical plane to at least  $45^\circ$  above and below the horizontal plane passing through the light sources, and
- 3) clamped in any selected vertical and horizontal positions.

**6.2.2** In order to facilitate manoeuvring the machine under test into the required position, that is with the eye position vertically above the centre of the semi-circle of vision marked on the surface of the test area, the following additional item is recommended, particularly when testing a machine without a cab:

- a plumb-bob suspended from a line running over a pulley attached to the ceiling or other rigid member situated over the test area, so that it is vertically above the centre point of the semi-circle of vision.

## 6.3 Tractor

**6.3.1** The tractor under test shall be unloaded and unballasted.

**6.3.2** The tyres fitted to the tractor shall be those recommended by the manufacturer, in new condition and inflated to the pressures recommended for road use.

## 6.4 Procedure

### 6.4.1 Angle of vision to the front/rear

**6.4.1.1** Set up the apparatus defining the eye position.

**6.4.1.2** Position the tractor on the test area with the eye position vertically above the centre of the appropriate semi-circle of vision.

**6.4.1.3** Locate the light sources, sighting instrument and/or camera with respect to the eye position. In the case of the camera, the reference point relative to the eye position shall be the intersection of its optical axis with the focal plane.

**6.4.1.4** Adjust the support so that the line joining the two light sources is perpendicular to the line joining the eye position and a component masking the semi-circle of vision to the front or to the rear, as appropriate.

**6.4.1.5** Switch on each light source in turn and

- a) record the positions and lengths of the chords denoting the presence of overlapping shadows on the vertical walls or screens;
- b) additionally, at the option of the manufacturer or if specified, determine and record obscuration of the ground plane by marking on the ground the area obscured by overlapping shadows (see figures 2 and 3).

**6.4.1.6** Repeat the procedures in 6.4.1.4 and 6.4.1.5 for each other masking component.

### 6.4.2 Angle of vision upwards

**6.4.2.1** Set up the apparatus defining the eye position.