

SVENSK STANDARD

SS-EN 1093-1:2008

Fastställt/Approved: 2008-12-15

Publicerad/Published: 2009-01-13

Utgåva/Edition: 2

Språk/Language: engelska/English

ICS:13.040.40; 13.110; 13.300; 14.070

Maskinsäkerhet – Beräkning av utsläpp av luftburna farliga ämnen – Del 1: Val av provningsmetoder

Safety of machinery – Evaluation of the emission of airborne hazardous substances – Part 1: Selection of test methods

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-68462>

Hitta rätt produkt och ett leveranssätt som passar dig

Standarder

Genom att följa gällande standard både effektiviserar och säkrar du ditt arbete. Många standarder ingår dessutom ofta i paket.

Tjänster

Abonnemang är tjänsten där vi uppdaterar dig med aktuella standarder när förändringar sker på dem du valt att abonnera på. På så sätt är du säker på att du alltid arbetar efter rätt utgåva.

e-nav är vår online-tjänst som ger dig och dina kollegor tillgång till standarder ni valt att abonnera på dygnet runt. Med e-nav kan samma standard användas av flera personer samtidigt.

Leveranssätt

Du väljer hur du vill ha dina standarder levererade. Vi kan erbjuda dig dem på papper och som pdf.

Andra produkter

Vi har böcker som underlättar arbetet att följa en standard. Med våra böcker får du ökad förståelse för hur standarder ska följas och vilka fördelar den ger dig i ditt arbete. Vi tar fram många egna publikationer och fungerar även som återförsäljare. Det gör att du hos oss kan hitta över 500 unika titlar. Vi har även tekniska rapporter, specifikationer och "workshop agreement".

Matriser är en översikt på standarder och handböcker som bör läsas tillsammans. De finns på sis.se och ger dig en bra bild över hur olika produkter hör ihop.

Standardiseringsprojekt

Du kan påverka innehållet i framtida standarder genom att delta i någon av SIS ca 400 Tekniska Kommittéer.

Find the right product and the type of delivery that suits you

Standards

By complying with current standards, you can make your work more efficient and ensure reliability. Also, several of the standards are often supplied in packages.

Services

Subscription is the service that keeps you up to date with current standards when changes occur in the ones you have chosen to subscribe to. This ensures that you are always working with the right edition.

e-nav is our online service that gives you and your colleagues access to the standards you subscribe to 24 hours a day. With e-nav, the same standards can be used by several people at once.

Type of delivery

You choose how you want your standards delivered. We can supply them both on paper and as PDF files.

Other products

We have books that facilitate standards compliance. They make it easier to understand how compliance works and how this benefits you in your operation. We produce many publications of our own, and also act as retailers. This means that we have more than 500 unique titles for you to choose from. We also have technical reports, specifications and workshop agreements.

Matrices, listed at sis.se, provide an overview of which publications belong together.

Standardisation project

You can influence the content of future standards by taking part in one or other of SIS's 400 or so Technical Committees.

Europastandarden EN 1093-1:2008 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av EN 1093-1:2008.

Denna standard ersätter SS-EN 1093-1, utgåva 1.

The European Standard EN 1093-1:2008 has the status of a Swedish Standard. This document contains the official English version of EN 1093-1:2008.

This standard supersedes the Swedish Standard SS-EN 1093-1, edition 1.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00.

Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), tel +46 8 555 520 00.

Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

SIS Förlag AB, SE 118 80 Stockholm, Sweden. Tel: +46 8 555 523 10. Fax: +46 8 555 523 11.

E-mail: sis.sales@sis.se Internet: www.sis.se

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 1093-1

December 2008

ICS 13.040.40

Supersedes EN 1093-1:1998

English Version

Safety of machinery - Evaluation of the emission of airborne hazardous substances - Part 1: Selection of test methods

Sécurité des machines - Evaluation de l'émission de substances dangereuses véhiculées par l'air - Partie 1 :
Choix des méthodes d'essai

Sicherheit von Maschinen - Bewertung der Emission von luftgetragenen Gefahrstoffen - Teil 1: Auswahl der Prüfverfahren

This European Standard was approved by CEN on 1 November 2008.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

Foreword.....	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Types of test methods.....	7
4.1 General.....	7
4.2 Nature of pollutant used	7
4.3 Nature of the test environment.....	8
4.3.1 General.....	8
4.3.2 Laboratory methods	8
4.3.3 Field method.....	8
4.4 Summary of methods	9
5 Basis for selection of test methods	9
5.1 General.....	9
5.2 Selection relative to the assessment parameter	9
5.3 Selection relative to the test environment	10
5.4 Selection relative to the nature of the pollutant	10
6 Statistical evaluation	11
6.1 Calculation of the mean	11
6.2 Confidence interval for the mean.....	11
Annex A (informative) Standards suitable for the measurement of fluid flow rates	12
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 98/37/EC	13
Annex ZB (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC	14
Bibliography	15

Foreword

This document (EN 1093-1:2008) has been prepared by Technical Committee CEN/TC 114 "Safety of machinery", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by June 2009, and conflicting national standards shall be withdrawn at the latest by December 2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 1093-1:1998.

For relationship with EU Directive(s), see informative Annexes ZA and ZB, which are integral parts of this document.

This part 1 of EN 1093 *Safety of machinery - Evaluation of the emission of airborne hazardous substances* belongs to a series of documents, the other parts of which are the following:

- Part 2: Tracer gas method for the measurement of the emission rate of a given pollutant;
- Part 3: Test bench method for the measurement of the emission rate of a given pollutant;
- Part 4: Capture efficiency of an exhaust system, tracer method;
- Part 6: Separation efficiency by mass, unducted outlet;
- Part 7: Separation efficiency by mass, ducted outlet;
- Part 8: Pollutant concentration parameter, test bench method;
- Part 9: Pollutant concentration parameter, room method;
- Part 11: Decontamination index.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

SS-EN 1093-1:2008 (E)

Introduction

The structure of safety standards in the field of machinery is as follows:

- **Type-A standards** (basic safety standards) giving basic concepts, principles for design, and general aspects that can be applied to all machinery;
- **Type-B standards** (generic safety standards) dealing with one safety aspect or one type of safeguard that can be used across a wide range of machinery:
 - Type-B1 standards on particular safety aspects (e.g. safety distances, surface temperature, noise);
 - Type-B2 standards on safeguards (e.g. two-hand controls, interlocking devices, pressure sensitive devices, guards);
- **Type-C standards** (machine safety standards) dealing with detailed safety requirements for a particular machine or group of machines.

This European Standard is a type-B standard as stated in EN ISO 12100-1.

The provisions of this European Standard can be supplemented or modified by a type-C standard.

For machines which are covered by the scope of a type-C standard and which have been designed and built according to the provisions of that standard, the provisions of that type-C standard take precedence over the provisions of this type-B standard.

The concentration level of substances resulting from emission of airborne hazardous substances from machines depends upon factors including:

- emission rate of airborne hazardous substances ("pollutants") from the machine under examination, depending of the type of process and the production rate of the machine;
- performance of the pollutant control system associated with the machine and, in the case of air recirculation, the performance of the separation system;
- surrounding conditions, especially the air flow pattern, which can reduce the pollution (efficient general ventilation) or increase it (disturbing air, crossdraughts);
- worker's location in relation to the machine and its pollutant control system, and taking into account the workers movements;
- quality of maintenance; poor quality has generally an adverse effect on the performance of the pollutant control and the separation systems.

This European Standard concerns the first two points in this list and forms only one part of a comprehensive risk assessment. It is not for a risk assessment of the workplace. Evaluation of the parameters defined in this European Standard leads to an evaluation of the performance of the machine and its associated pollutant control system.

This European Standard can be used as a part of verification described in EN 626-2.

1 Scope

This European Standard specifies parameters which can be used for the assessment of the emission of pollutants from machines or the performance of the pollutant control systems integrated in machines. It gives guidance on the selection of appropriate test methods according to their various fields of application and types of machines including the effects of measures to reduce exposures to pollutants. The test methods are given in additional parts of this European Standard (see Table 1 and Annex A).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 626-2, *Safety of machinery – Reduction of risks to health from hazardous substances emitted by machinery – Part 2: Methodology leading to verification procedures*

EN ISO 12100-1:2003, *Safety of machinery – Basic concepts, general principles for design – Part 1: Basic terminology, methodology (ISO 12100-1:2003)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN ISO 12100-1:2003 and the following apply.

3.1 uncontrolled emission rate of a given pollutant

\dot{m}_u

mass of pollutant emitted from the machine into the space around the machine per unit of time

NOTE Any measures to reduce the air pollution around the machine (e.g. capture devices, containment equipment, wetting process) should not be used or should be de-activated.

3.2 controlled emission rate of a given pollutant

\dot{m}_k

mass of pollutant emitted from the machine into the space around the machine per unit of time, taking into account the effects of measures to reduce the air pollution

NOTE Any measures to reduce the air pollution around the machine (e.g. capture devices, containment equipment, wetting process) should be used or activated.

SS-EN 1093-1:2008 (E)

3.3 capture efficiency

η_c

<pollutant control system> ratio of the mass flow rate of a given pollutant directly collected by the pollutant control system to the uncontrolled mass flow rate of this pollutant emitted from the machine

NOTE 1 The capture efficiency, as a percentage, can be calculated by the following equation:

$$\eta_c = \frac{\dot{m}_u - \dot{m}_k}{\dot{m}_u} \times 100 \quad (1)$$

This equation is applicable only if $\dot{m}_u - \dot{m}_k$ represents the pollutant mass flow rate directly captured. This parameter is not usable when the amount of emission is affected by the control system.

NOTE 2 Where the pollutant control system is an exhaust system and provided comparable discharge and flow patterns of the real pollutant can be simulated by a tracer technique, the equation becomes:

$$\eta_c = \frac{q_c}{q_E} \times 100 \quad (2)$$

where

q_c flow rate of tracer collected by exhaust system during operation;

q_E flow rate of tracer emitted (measured by emitting the tracer directly into exhaust system during the first phase)

NOTE 3 For further details, see EN 1093-4:1996+A1:2008, Clause 5.

3.4 separation efficiency by mass

η_s

<air cleaning system> ratio of the mass of pollutant retained by the air cleaning system (m_3) to the mass of pollutant entering the air cleaning system (m_1) during a given period

NOTE 1 For special applications the number of fibres or particles is measured instead of the mass.

NOTE 2 The separation efficiency of an air cleaning system, as a percentage, can be calculated by the following equation:

$$\eta_s = \frac{m_3}{m_1} \times 100 \quad (3)$$

NOTE 3 In certain cases it can be necessary to consider only that part of pollutants (e.g. size of particles) which is actually hazardous for exposed persons; e.g. separation efficiency of a separation system against hazardous dust is measured as a function of particle size – otherwise the results are possibly not reliable for health and safety purposes.

3.5 pollutant concentration parameter

P_c

the measured concentration of a given pollutant in defined position(s) near the machine

3.6 decontamination index

I_A

the average of the ratio, obtained at a number of specified locations in the surroundings, of the ambient air quality improvement to the real pollutant mean concentration with the pollutant control system not in operation

NOTE 1 Corrections can be necessary to take into account air pollution caused by other operations ("the background level").

NOTE 2 The decontamination index can be calculated by the following equation:

$$I_A = \frac{1}{n} \sum_{i=1}^n \frac{C_{ai} - C_{mi}}{C_{ai} - C_{fi}} \quad (4)$$

where

C_{ai} real pollutant concentration measured at specified location in the surrounding under the following condition: machine in operation, pollutant control system not in operation;

C_{mi} real pollutant concentration measured at specified location in the surrounding under the following condition: machine and pollutant control system in operation;

C_{fi} real pollutant concentration measured at specified location in the surrounding under the following condition: machine and pollutant control system not in operation ("the background level");

n number of specified locations

NOTE 3 When the "background level" is negligible, the decontamination index reduces to:

$$I_A = 1 - \frac{1}{n} \sum_{i=1}^n \frac{C_{mi}}{C_{ai}} \quad (5)$$

4 Types of test methods

4.1 General

When particle size distribution is determined at the same time as pollutant concentration, an assessment parameter for each size fraction can be defined. For the determination of each assessment parameter (see Clause 3), different test methods can be considered. The test methods should be selected according to the following criteria:

- nature of pollutant used;
- nature of the test environment.

4.2 Nature of pollutant used

As far as possible, the real pollutant should be used for the testing. However, in some cases tracer techniques allow a more convenient testing. The addition of tracer material to the real pollutant requires several conditions to be met, in particular comparable discharge and flow patterns of the real pollutant and the tracer material, respectively.

Depending on the test method, two types of pollutants shall be considered:

- real pollutant which may be an aerosol (solid or liquid) or a gas;