

SVENSK STANDARD

SS-ISO 18195:2019



Fastställt/Approved: 2019-04-01
Utgåva/Edition: 1
Språk/Language: engelska/English
ICS: 27.010; 27.120.10; 27.120.20

Metod för analys av brandsektionering i vattenkylda reaktorer (ISO 18195:2019, IDT)

Method for the justification of fire partitioning in water cooled nuclear power plants (NPP) (ISO 18195:2019, IDT)

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-80010725>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.

Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Den internationella standarden ISO 18195:2019 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 18195:2019.

The International Standard ISO 18195:2019 has the status of a Swedish Standard. This document contains the official English version of ISO 18195:2019.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Kärnenergi, SIS/TK 405.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

Contents

Page

Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	1
3.1 Terms and definitions.....	2
3.2 Symbols.....	4
3.3 Abbreviated terms.....	5
4 Method for justification of nuclear safety fire partitioning: global approach	5
4.1 Objective of the method.....	5
4.1.1 The basis of design: standard fire resistance tests.....	5
4.1.2 Aim, limitations, and precautions.....	6
4.1.3 Minimum requirements concerning the qualification of the method practitioners.....	7
4.2 General principle of the method	8
4.3 Design of the partitioning: justification of the adequate performance of fire barriers.....	10
4.4 Fire barriers and structural elements	10
4.5 Overall flowchart (flowchart 1).....	10
5 Determination of the design basis fire temperature curve (room fire curve)	11
5.1 General considerations in room fire scenarios.....	11
5.1.1 Typical development stages of a compartment fire.....	12
5.2 Defining the design basis fire temperature curve for a room.....	13
5.3 Requirements concerning calculation tools.....	14
5.4 Assumptions and input data for numerical calculations.....	15
5.4.1 Fixed automatic fire fighting system (credited or not).....	15
5.4.2 Modeling assumptions.....	16
5.4.3 Characteristics of a room.....	16
5.4.4 Nature of fuels	17
5.4.5 Fire scenarios.....	18
5.4.6 Recommended value for pyrolysis rates	23
5.5 Design basis fire temperature curve calculation process.....	23
5.5.1 Data input.....	23
5.5.2 Modelling of the fire volume and scenarios.....	23
5.5.3 Modelling options	23
5.6 Determination of the fire temperature curve.....	24
6 Determination of the performance of fire barriers (performance curve diagram)	26
6.1 Principles.....	26
6.2 Characterization of the performance diagram: global methodology	26
6.3 Phase 1: analysis of the standard test.....	27
6.4 Phase 2 branch A: determination by calculation	28
6.4.1 Study approach	28
6.4.2 Selection of representative experimental curves.....	29
6.4.3 Calculation tools and choice of the modelling.....	29
6.4.4 Thermal properties of materials	30
6.4.5 Plotting performance curves from the reference curves	32
6.4.6 Plotting “steady state” curves.....	34
6.4.7 Plotting the performance diagram	34
6.5 Phase 2 BRANCH B: working out a new family system.....	34
6.5.1 Study approach for branch B.....	34
6.5.2 Experimental check (step 5B)	35
6.6 Phase 2 branch C: specific characterization tests.....	36
6.7 Alternative performance curves.....	37

6.8	Performance curve diagram.....	37
6.9	Validation of the models.....	37
7	Uncertainty and sensitivity.....	37
7.1	Use of average values (zone model vs. CFD model).....	38
7.2	Uncertainties and sensitivities in fire temperature curve calculation.....	38
7.3	Uncertainties and sensitivities in the performance curve process.....	38
Annex A (informative) Spreading criterion PFG/PFL (examples).....		40
Annex B (informative) Value examples for fire scenarios		42
Annex C (informative) Loss of classification criteria : examples.....		51
Annex D (informative) Example of performance diagram of a cable fire-wrap		52
Bibliography.....		65

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 85, *Nuclear energy, nuclear technologies, and radiological protection*, Subcommittee SC 6, *Reactor Technology*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This corrected version of ISO 18195:2019 incorporates the following corrections:

- In 5.4.5.4, a few formatting corrections were made;
- In 6.4.7, Figure 13 has been corrected and the key modified accordingly.

Introduction

This document is intended to provide a technical specification to verify the adequacy of the performance of fire partitions in nuclear power plants. The intended audience of this document are fire safety engineers and project designers. Nuclear authorities are also concerned considering that this method is to be used in the process of fire hazard nuclear safety demonstration. The method presented herein includes a combination of standardized testing and ad hoc testing with numerical and empirical calculations. Users of this document are expected to be appropriately qualified and competent in the fields of fire safety engineering, risk assessment and fire resistance standardization.

This document specifies a new methodology to Nuclear Power Plant (NPP) designers, fire safety professionals and nuclear safety authorities. This methodology aims to verify the adequacy of the performance of fire barriers in nuclear power plants in order to avoid fire propagation. This method is a potential tool for risk-informed, performance-based assessment.

NOTE This method is based on the EPRESSI method developed by EDF in collaboration with Efectis France fire safety laboratory in France for EPR reactors^[39].

Method for the justification of fire partitioning in water cooled nuclear power plants (NPP)

1 Scope

The document provides:

- guidelines for determining the thermal effects to consider on fire barriers inside a given room;
- guidelines for determining the global performance of the fire barriers based on standard test characterization;
- guidelines for assessing the need for additional tests to verify the robustness of the solution.

Requirements of applicable standards, numerical tools validation and verification (V&V), and the expected qualification of fire resistance laboratories are detailed.

The limitations of the method's applicability and scope are discussed.

The purpose and justification of this document is to describe a new methodology for the verification of the efficiency of fire barriers, which is initially based on a standardized fire resistance test.

The significance of this work relates to the fact that the present methodology will enhance the level of safety by providing more realism to hazards analysis in combination with standardized test data. It completes the standard ISO-fire rating required for justifying the performance.

The most relevant benefit of this method concerns the determination of the global performance of a barrier in a fire of extended duration compared to the classification given by the ISO-fire rating.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 12749-2, *Nuclear energy, nuclear technologies, and radiological protection — Vocabulary — Part 2: Radiological protection*

ISO 12749-3, *Nuclear energy, nuclear technologies, and radiological protection — Vocabulary — Part 3: Nuclear fuel cycle*

ISO 12749-4, *Nuclear energy, nuclear technologies, and radiological protection — Vocabulary — Part 4: Dosimetry for radiation processing*

ISO 12749-5, *Nuclear energy, nuclear technologies, and radiological protection — Vocabulary — Part 5: Nuclear reactors*

ISO 13943, *Fire safety — Vocabulary*

ISO/IEC 17025, *General requirements for the competence of testing and calibration laboratories*

3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the terms and definitions given in ISO 13943, ISO 12749-2, ISO 12749-3, ISO 12749-4, and ISO 12749-5 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <http://www.electropedia.org/>

3.1 Terms and definitions

3.1.1

credited combustible

part of the potential combustible material that will actually participate to the fire development

3.1.2

design basis fire

fire which may break out in any fire source of the plant and which has the severest consequences (duration, severity)

Note 1 to entry: For a given room, it is a fire taking into account all available fuel in this room liable to burn. Its characteristics are calculated taking into account the characteristics of the rooms and fuels.

3.1.3

fire volume

volume inside a building, composed of one or several rooms and designed to prevent the extension of a fire through its boundaries

Note 1 to entry: One of the means of preventing the extension of the fire is to keep it within a limited volume, either physically, by partitions opposing the fire propagation, either spatially, by boundaries associated with the remoteness of the components, with active protection systems (sprinklers), or with passive protection systems (structural features, cable wraps).

3.1.4

fire cell

fire volume (3.1.3) consisting of one or more rooms, bounded by separations guaranteeing that a fire occurring inside cannot extend to the outside or that one occurring on the outside cannot spread to the inside for a given period of time

Note 1 to entry: The boundaries of a fire cell may be either fire-resistant physical barriers, wall, ceiling and floor or *spatial separation* (3.1.15) through openings with a certain configuration and distance rules between combustible sources guaranteeing geographical separations with adjacent rooms and other fire areas. The non-propagation assumption has to be verified (by fire influence studies).

3.1.5

fire compartment

fire volume (3.1.3) consisting of one or more rooms, bounded by material *partitions* (3.1.10) whose fire resistance guarantees that a fire occurring inside cannot extend to the outside or that one occurring on the outside cannot spread to the inside for a given period of time

Note 1 to entry: All the partitions of a fire compartment shall be fire-resistant physical barriers, walls, ceilings, or floors.

3.1.6

fire resistance rating

time during which the fire *partitioning elements* (3.1.9) (partitions, walls, floors, doors, dampers, caulking of penetrations, enclosures of cable racks, etc.) can fulfil their assigned role, despite the effect of a standard fire

3.1.7

low heat load threshold

LHLT

threshold which is introduced to avoid calculations in case of rooms that have too small quantity of combustible material and are neither PFL nor PFG

Note 1 to entry: See 5.4.5.3.

3.1.8

“neither PFG nor PFL” criterion

criterion that is met when the quantity of combustible material is not sufficient to generate a significant fire and does not present risks for spreading to secondary fire sources

Note 1 to entry: By extension, a room is said to be “neither PFG nor PFL” when the concentration of combustible masses in it is not enough to generate a widespread fire (with no necessity of further verification).

3.1.9

partitioning elements

features (partitions, fire walls, ceilings, floors, ducts, seals of openings such as doors, shutters, dampers, hatches as well as seals of cable bushings and piping sleeves) which make up a *partition* ([3.1.10](#))

3.1.10

partition

set of *partitioning elements* ([3.1.9](#)) which fully bound the relevant area by *physical separation* ([3.1.13](#))

3.1.11

possibility of a fire getting generalized

PFG criterion

criterion for a fire source when its burning is likely to result in flashover and a generalized fire

Note 1 to entry: By extension, a room is said to be PFG when a fire breaking out in an unfavourable part of the room may result in flashover and generalized fire in the whole room.

3.1.12

all possible fires remaining localized

PFL criterion

criterion for a fire source when its burning shall not result in flashover or propagate to other parts of the *room* ([3.1.14](#))

Note 1 to entry: A fire meeting this criterion remains localised and goes out spontaneously. By extension, a room is said to be PFL when a fire breaking out at the most unfavourable part of the room cannot result in flashover nor propagate to other parts of the room; it remains localised and goes out spontaneously.

Note 2 to entry: The hypothesis of a fire source or room being PFL assumes a single fire source representation but the non-propagation to other fire sources inside or outside the room need a confirmation using a spread temperature threshold (STT).

3.1.13

physical separation

installation of two items of equipment in two distinct *rooms* ([3.1.14](#)) of which at least one is inside a *fire compartment* ([3.1.5](#)), or protection of one of them by an insulating thermal casing to prevent the simultaneous loss of both items of equipment due to a single fire

3.1.14

room

<common meaning> single volume identified by the user inside the building with no structural separation assumed inside

Note 1 to entry: Its boundaries may or may not be completely closed.

3.1.15

spatial separation

installation of two items of equipment in different *rooms* ([3.1.14](#)) or at an adequate distance free of any fuel to prevent fire from spreading