

SVENSK STANDARD

SS-ISO 20574:2019



Fastställt/Approved: 2019-09-24
Utgåva/Edition: 1
Språk/Language: engelska/English
ICS: 43.060.50

Vägfordon – Provningsmetod för hållbarhet hos startmotor i start/stopp-system (ISO 20574:2019, IDT)

Road vehicles – Durability test method for starter motor for stop and start system (ISO 20574:2019, IDT)

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-80016649>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.



Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.


Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Den internationella standarden ISO 20574:2019 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 20574:2019.

The International Standard ISO 20574:2019 has the status of a Swedish Standard. This document contains the official English version of ISO 20574:2019.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för EI- och elektronikutrustning för vägfordon, SIS/TK 240.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	1
4 Planning of durability test	4
4.1 Determination of durability test types	4
4.2 Determination of durability test conditions	4
4.3 Definition of cranking time, overrunning time	7
5 Test bench equipment and information	9
5.1 Test bench structure.....	9
5.2 Minimum requirements of test bench	9
5.3 Test bench measuring capabilities and channel list	10
5.4 Test stop criteria	10
6 Detailed test procedures	11
6.1 Test procedure	11
6.1.1 General.....	11
6.1.2 Installation and setup stage for engine or engine simulator.....	11
6.1.3 Pre-check stage	12
6.1.4 Test execution stage	12
6.1.5 Post processing and reporting stage.....	13
7 Supplemental test methods	13
7.1 Brush temperature calibration	13
7.2 Starter motor input V-I curve and verification	15
7.3 Brush length measurement.....	16
7.4 Pinion to ring gear axial gap	17
Annex A (normative) Test bench structure (Type 1)	18
Annex B (normative) Test bench structure (Type 2)	19
Annex C (normative) Test bench structure (Type 3 and 4)	20
Annex D (informative) Summary of reporting items after the test	21

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 22, *Road vehicles*, Subcommittee SC 32, *Electrical and electronic components and general system aspects*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

Stop and start systems contribute to fuel saving by stopping the engine when its operation is not needed, and to start the engine automatically when its operation is needed. The more frequent starting of the engine requires higher durability of the starter motor. Since there is no standard to evaluate the durability of starter motors for stop and start systems, individual specifications are used by engine and/or vehicle manufacturers and starter motor manufacturers. Because the stop and start systems require much more frequent starter motor operations, the testing period is much longer compared to conventional starter motors.

In addition to engine and/or vehicle manufacturers and starter motor manufacturers, testing companies also began to conduct tests. In order to carry out the time-consuming test accurately and to use the test results effectively, the test procedure in this document includes how to summarize the test results.

Road vehicles — Durability test method for starter motor for stop and start system

1 Scope

This document defines requirements and recommendations for starter motor durability testing of 12 V start systems for internal combustion engines. This includes test methods, test procedures and capabilities of test benches.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 8856, *Road vehicles — Electrical performance of starter motors — Test methods and general requirements*

3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1

stop and start system

system to stop the engine when its operation is not needed, and to start the engine automatically when its operation is needed

3.2

manual start

event when the engine is started manually by the driver

3.3

automatic start

event when the engine is started by the stop and start system automatically

3.4

dummy starter motor

starter motor used for installation purpose only

3.5

calibration starter motor

starter motor used for calibration of test condition, which is equipped for measuring temperatures of its components

3.6

engine simulator

device which simulates engine behaviour during engine start

3.7

battery simulator

electrical power supply equipment which simulates battery behaviour

SS-ISO 20574:2019 (E)

3.8

engine mount

mechanical frame to support engine and gearbox

3.9

number of test start cycles

counted durability test start cycles

3.10

remaining brush length

length of brush after the test

3.11

usable brush length

length of brush that is available to be consumed

3.12

initial brush length

length of brush before starting the test

3.13

vehicle manufacturer

company which designs and produces vehicles

3.14

engine manufacturer

company which designs and produces internal combustion engines

3.15

starter motor manufacturer

company which designs and produces starter motors

3.16

cranking

condition in which the starter motor rotates the engine

3.17

overrunning

condition in which the engine rotates the starter motor pinion before starter motor OFF

3.18

engine ECU

electronic control unit for controlling internal combustion engine operation

3.19

starter solenoid

electromagnetic component of starter motor to move pinion and to switch electric motor

3.20

bi-control solenoid

starter solenoid which is able to control separately pinion movement and to switch electric motor

3.21

bench controller

device which is capable of controlling required test bench functions

3.22

nominal power

P_{nom}

power declared by the starter motor manufacturer corresponding to the maximum power output at the reference temperature when determined according to ISO 8856

3.23

battery internal and line resistance

R_{BL}

sum of power supply (battery or battery simulator) internal resistance and total resistance of external line (positive and negative sides and connections)

3.24

device under test

DUT

starter motor used for durability test

3.25

change of mind

CoM

start event before complete engine stall

3.26

starter motor voltage

U_{STR}

voltage at battery terminal of starter motor

3.27

starter motor current

I_{STR}

current drawn by starter motor

3.28

starter motor open circuit voltage

U_{0_STR}

voltage at starter motor terminals without electrical load

3.29

virtual starter motor voltage

$U_{0_STR_v}$

virtual starter motor voltage at $I_{STR} = 0A$ derived from V-I curve

3.30

battery internal resistance

R_B

power supply (battery or battery simulator) resistance

3.31

line resistance

R_L

total resistance of external line (positive and negative sides and connections)

3.32

front end accessory drive

FEAD

equipment driven by belt which is connected to engine

3.33

starter motor temperature at control point

$T_{control}$

temperature measured at defined control point location

EXAMPLE At starter motor yoke surface.

3.34 temperature of starter motor brush

T_{brush}
 temperature measured inside of starter motor brush

3.35 pinion to ring gear axial gap

d_{prg}
 axial distance from front surface of pinion to ring gear at rest condition

3.36 starter motor input curve

V-I curve
 straight line calculated from starter motor voltage vs starter motor current diagram defining starter motor input conditions

4 Planning of durability test

4.1 Determination of durability test types

The durability test is performed with an engine simulator or an engine. The following test types can be selected. See [Table 1](#) for comparison of each test type.

- 1) Engine, using bench controller to control fuel/spark to specifically achieve pre-determined cranking time and overrunning time (see [Table 3](#)).
- 2) Engine, using its engine ECU to control the test parameters.
- 3) Engine simulator, using engine waveform data provided by engine and/or vehicle manufacturers as input to simulator (for cranking time, overrunning time, or torque) (see [Table 3](#)).
- 4) Engine simulator, using synthetic pattern or engine simulation model where starter motor manufacturer or engine and/or vehicle manufacturers define values for torque, cranking and overrunning behaviour (see [Table 3](#)).

Table 1 — Overview of test types

Test type	Starter load	Starter load characteristic	Reference
1	Engine	Engine using bench controller	Annex A
2		Engine using engine ECU	Annex B
3	Engine Simulator	Engine simulation using engine waveform data	Annex C
4		Engine simulation using synthetic pattern	Annex C

4.2 Determination of durability test conditions

The starter motor manufacturer and engine and/or vehicle manufacturers should define the test conditions according to the test planning matrix shown in [Table 2](#).

The following items should be specifically considered:

- 1) In case of engine simulator, multiple starter motors can be tested simultaneously with the same ring gear. In that case, the orientation of the starter motors deviate from those of the target application. Hence, the usage of multiple starter motors shall correspond to the test purpose (e.g. verification of brush durability but not verification of pinion and ring gear durability).

- 2) The starter motor manufacturer and engine and/or vehicle manufacturers should agree starter motor temperature level during the durability test. Different approaches to define temperature level are established.

For example:

- test at maximum brush temperature defined by starter motor manufacturer;
- test at maximum brush temperature derived from vehicle real drive cycle; and
- test at an average brush temperature derived from brush temperature distributions of vehicle real drive cycle.

Each approach covers different testing purposes such as focusing on thermal stress, test duration, mechanical loads or balanced field representation.

- 3) The starter motor manufacturer and engine and/or vehicle manufacturers should define the test pass criteria and define test stop criteria according to [Table 6](#).
- 4) Additional test conditions may be defined and shall be documented in test planning matrix.

For example:

- always using “100 % new” battery for every test;
- testing with maximum pinion to ring gear axial gap; and
- number and orientation of starter motors mounted to engine simulator ring gear.

Table 2 — Test planning matrices

Test planning matrix (1/3)				Reference
Test type (test type #1 to #4)				4.1
Target test duration (number of test start cycles)				
Test sequence		__ x[M/S] + __ x[A/S] + __ x[CoM] + __ x[A/S] + __ x[CoM]		
Manual start [M/S]	t ₁	s	t ₂	Table 3 including NOTE 1
	t ₃	s	t ₄	
	t ₅	s	n ₁ min ⁻¹	
Automatic start [A/S]	t ₆	s	t ₇	Table 3 includ- ing NOTE 2
	t ₈	s	t ₉	
	t ₁₀	s	n ₂ min ⁻¹	
CoM start [CoM]	n ₃ min ⁻¹		n ₄ min ⁻¹	Table 3 including NOTE 3
	t ₁₁	s		