


SVENSK STANDARD

SS-ISO 668:2020

Containrar serie 1 – Indelning, mått och bruttovikter
(ISO 668:2020, IDT)

Series 1 freight containers – Classification, dimensions and
ratings (ISO 668:2020, IDT)



sis Svenska
Institutet för
Standarder

Language: engelska/English

Edition: 5

This preview is downloaded from www.sis.se. Buy the entire
standard via <https://www.sis.se/std-80019239>

Den här standarden kan hjälpa dig att effektivisera och kvalitetssäkra ditt arbete. SIS har fler tjänster att erbjuda dig för att underlätta tillämpningen av standarder i din verksamhet.

SIS Abonnemang

Snabb och enkel åtkomst till gällande standard med SIS Abonnemang, en prenumerationstjänst genom vilken din organisation får tillgång till all världens standarder, senaste uppdateringarna och där hela din organisation kan ta del av innehållet i prenumerationen.

Utbildning, event och publikationer

Vi erbjuder även utbildningar, rådgivning och event kring våra mest sålda standarder och frågor kopplade till utveckling av standarder. Vi ger också ut handböcker som underlättar ditt arbete med att använda en specifik standard.

Vill du delta i ett standardiseringsprojekt?

Genom att delta som expert i någon av SIS 300 tekniska kommittéer inom CEN (europeisk standardisering) och/eller ISO (internationell standardisering) har du möjlighet att påverka standardiseringsarbetet i frågor som är viktiga för din organisation. Välkommen att kontakta SIS för att få veta mer!

Kontakt

Skriv till kundservice@sis.se, besök [sis.se](https://www.sis.se) eller ring 08 - 555 523 10

© Copyright/Upphovsrätten till denna produkt tillhör Svenska institutet för standarder, Stockholm, Sverige. Upphovsrätten och användningen av denna produkt regleras i slutanvändarlicensen som återfinns på [sis.se/slutanvandarlicens](https://www.sis.se/slutanvandarlicens) och som du automatiskt blir bunden av när du använder produkten. För ordlista och förkortningar se [sis.se/ordlista](https://www.sis.se/ordlista).

© Copyright Svenska institutet för standarder, Stockholm, Sweden. All rights reserved. The copyright and use of this product is governed by the end-user licence agreement which you automatically will be bound to when using the product. You will find the licence at [sis.se/enduserlicenseagreement](https://www.sis.se/enduserlicenseagreement).

Upplysningar om sakinnehållet i standarden lämnas av Svenska institutet för standarder, telefon 08 - 555 520 00. Standarder kan beställas hos SIS som även lämnar allmänna upplysningar om svensk och utländsk standard.

Standarden är framtagen av kommittén för Lastsäkring - Godstransporter, SIS/TK 591.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

Den internationella standarden ISO 668:2020 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 668:2020.

Denna standard ersätter SS-ISO 668:2016, utgåva 4 och SS-ISO 668:2016/Amd 1:2016, utgåva 1 och SS-ISO 668:2016/Amd 2:2016, utgåva 1

The International Standard ISO 668:2020 has the status of a Swedish Standard. This document contains the official English version of ISO 668:2020.

This standard supersedes the SS-ISO 668:2016, edition 4 and SS-ISO 668:2016/Amd 1:2016, edition 1 and SS-ISO 668:2016/Amd 2:2016, edition 1

Contents

Page

Foreword	v
1 Scope.....	6
2 Normative references	6
3 Terms and definitions.....	6
4 Classification and designation	7
5 Dimensions, tolerances and ratings.....	8
5.1 Reference temperature for measurements.....	8
5.2 External dimensions, tolerances and ratings.....	8
5.2.1 External dimensions and tolerances.....	8
5.2.2 Ratings	8
5.2.3 Gooseneck tunnels.....	9
5.3 Internal dimensions and door openings.....	9
5.3.1 Dimensions with projecting top corner fitting.....	9
5.3.2 General cargo containers for general purposes (see ISO 1496-1).....	9
5.3.3 Thermal containers (see ISO 1496-2).....	9
5.3.4 Other types of container	10
5.4 Corner fitting locations	10
Annex A (normative) Corner fittings	12
Annex B (normative) Details of requirements for load transfer areas in base structures of containers	14
Annex C (normative) Dimensions of gooseneck tunnels	20
Bibliography.....	22

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 104, *Freight containers*, Subcommittee SC 1 *General purpose containers*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

This seventh edition cancels and replaces the sixth edition (ISO 668:2013), which has been technically revised. It also incorporates the Amendments ISO 668:2013/Amd1:2016 and ISO 668:2013/Amd2:2016.

The main changes compared to the previous edition are the inclusion of the Amendments.

Series 1 freight containers — Classification, dimensions and ratings

1 Scope

This document establishes a classification of series 1 freight containers based on external dimensions, and specifies the associated ratings and, where appropriate, the minimum internal and door opening dimensions for certain types of containers.

These containers are intended for intercontinental traffic.

This document summarizes the external and some of the internal dimensions of series 1 containers. The dimensions of each type of container are defined in the appropriate part of ISO 1496, which is the authoritative document for internal container dimensions.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 830, *Freight containers — Vocabulary*

ISO 6346, *Freight containers — Coding, identification and marking*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 830 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

3.1 freight container

article of transport equipment:

- a) of a permanent character and accordingly strong enough to be suitable for repeated use;
- b) specially designed to facilitate the carriage of goods by one or more modes of transport, without intermediate reloading;
- c) fitted with devices permitting its ready handling, particularly its transfer from one mode of transport to another;
- d) designed so as to be easy to fill and empty;
- e) having an internal volume of 1 m³ (35,3ft³) or more

Note 1 to entry: The term "freight container" does not include vehicles or conventional packing.

3.2 ISO container

freight container (3.1) complying with all relevant ISO container standards in existence at the time of its manufacture

3.3
rating
R

gross mass of a container which is both the maximum mass for operation and the minimum mass for testing

Note 1 to entry: In some countries, in order to conform to current commercial practice, the term "weight" is used (incorrectly) instead of "mass".

3.4
nominal

<dimensions> disregarding tolerances and rounded to the nearest convenient whole number, by which a container may be identified

Note 1 to entry: Nominal dimensions are usually expressed in imperial units.

3.5
internal

<dimensions> relating to the largest unobstructed rectangular parallelepiped which can be inscribed in the container if inward protrusions of the top corner fittings are disregarded

Note 1 to entry: Except where stated otherwise, the term "internal dimensions" is synonymous with the term "unobstructed internal dimensions".

3.6
door opening

size of the (end) door aperture, i.e. width and height dimensions of the largest parallelepiped which could possibly be passed into the container through the door aperture in question

4 Classification and designation

Series 1 freight containers have a uniform width of 2 438 mm (8 ft).

The nominal lengths are listed in [Table 1](#).

Containers 2 896 mm (9 ft 6 in) in height are designated 1EEE, 1AAA and 1BBB.

Containers 2 591 mm (8 ft 6 in) in height are designated 1EE, 1AA, 1BB and 1 CC.

Containers 2 438 mm (8 ft) in height are designated 1A, 1B, 1C and 1D.

Containers less than 2 438 mm (8 ft) in height are designated 1AX, 1BX, 1 CX and 1 DX.

NOTE The letter "X" used in the designation has no specific connotation other than to indicate that the height of the container is between 0 mm and 2 438 mm (8 ft).

Table 1 — Nominal lengths

Freight container designation	Nominal length	
	m	ft
1EEE 1EE	13,7 ^a	45 ^a
1AAA 1AA 1A 1AX	12,2 ^a	40 ^a
1BBB 1BB 1B 1BX	9,1	30
1CCC 1CC 1C 1CX	6,1	20
1D 1DX	3,00	10
^a Legal limitations to the overall length of vehicle and load can exist in certain countries.		

5 Dimensions, tolerances and ratings

5.1 Reference temperature for measurements

The dimensions and tolerances apply when measured at the temperature of 20 °C (68 °F); measurements taken at other temperatures shall be adjusted accordingly.

5.2 External dimensions, tolerances and ratings

5.2.1 External dimensions and tolerances

The external dimensions and permissible tolerances given in [Table 2](#) are applicable to all types of containers, except that a reduced height is permissible for tank, open top, bulk, platform and platform-based type containers.

5.2.2 Ratings

The ratings given in [Table 2](#) are applicable to all types of containers, except that for particular traffic, higher values are permissible for containers of any type specified in [Table 2](#). Such containers are considered as ISO containers provided that their maximum gross mass, *R*, does not exceed 36 000 kg and that they are tested and marked to their actual rating, *R* (see [3.3](#)).

WARNING — Recognizing that there will always be a need for special containers for particular traffic, attention is drawn to the fact that numerous containers exist which have length and width dimensions similar to those of ISO series 1 containers but have ratings and/or heights in excess of those defined by this document. This can include containers having maximum gross masses

in excess of the ratings in Table 2. They may not, therefore, be fully intermodal worldwide and their operation can require special arrangements.

5.2.3 Gooseneck tunnels

Gooseneck tunnels shall be provided as mandatory features in containers 1EEE, 1AAA, and may be provided as optional features in containers 1EE, 1AA, 1A and 1AX. The dimension of gooseneck tunnels shall be in accordance with Annex C. The base structure of a container shall be in accordance with Annex B.

5.3 Internal dimensions and door openings

5.3.1 Dimensions with projecting top corner fitting

Where a top corner fitting projects into the internal space (specified by Table 3), that part of the corner fitting projecting into the container shall not be considered as reducing the size of the container.

5.3.2 General cargo containers for general purposes (see ISO 1496-1)

5.3.2.1 General

The type code numbers shall be in accordance with ISO 6346.

5.3.2.2 Minimum internal dimensions

Internal dimensions of containers shall be as large as possible but, in any case, greater or equal to those given in Table 3 except for the following:

- containers type G3, having partial opening(s) in the side(s), shall comply with the requirements for minimum internal length and height as given in Table 3;
- containers type G9, when fitted with roof opening(s), shall comply with the requirements for minimum internal length and width as given in Table 3;
- closed, ventilated containers type V2, when fitted internal ventilation equipment, shall comply with the requirements for minimum internal height and width as given in Table 3.

5.3.2.3 Minimum door opening dimensions

Closed-type containers designated 1A, 1B, 1C and 1D shall have a door opening, preferably having dimensions equal to those of the internal cross-section (height and width) of the containers and, in any case, not less than the values given in Table 3.

Closed-type containers designated 1EE, 1AA, 1BB and 1CC shall have a door opening, preferably having dimensions equal to those of the internal cross-section (height and width) of the containers and, in any case, not less than the values given in Table 3.

Closed-type containers designated 1EEE, 1AAA and 1BBB shall have a door opening, preferably having dimensions equal to those of the internal cross-section (height and width) of the containers and, in any case, not less than the values given in Table 3.

5.3.3 Thermal containers (see ISO 1496-2)

The internal dimensions and door openings of thermal containers shall be as large as possible. Door openings shall preferably have dimensions equal to those of the internal cross-section of the containers.

The internal dimensions shall be measured from inner faces of battens, bulkheads, ceiling air ducts, floor air ducts, etc., where fitted.

SS-ISO 668:2020 (E)

The minimum internal width shall be 2 200 mm (7 ft 2 5/8 in) for all thermal container types.

5.3.4 Other types of container

The internal dimensions, door openings and end openings (if any) shall be as large as possible.

5.4 Corner fitting locations

Centre-to-centre distances (length and width) and diagonal tolerances for corner fittings shall be as in Annex A.

Table 2 — External dimensions, permissible tolerances and ratings for series 1 freight containers

Freight container designation	Length, <i>L</i>			Width, <i>W</i>			Height, <i>H</i>			Rating, <i>R</i> ^a (gross mass)				
	tol.		tol.	tol.		tol.	tol.		tol.	kg	lb			
	mm	ft and in	in	mm	ft	in	mm	ft and in	in					
1EEE	13 716	0 -10	45'	0 -3/8	2 438	0 -5	8	0 -3/16	2 896 ^b	0 -5	9' 6''	0 -3/16	30 480 ^a	67 200 ^a
1EE										2 591 ^b	0 -5	8' 6''	0 -3/16	30 480
1AAA	12 192	0 -10	40'	0 -3/8	2 438	0 -5	8	0 -3/16	2 896 ^b	0 -5	9' 6'' ^b	0 -3/16	30 480 ^a	67 200 ^a
1AA									2 591 ^b	0 -5	8' 6'' ^b	0 -3/16		
1A									2 438	0 -5	8'	0 -3/16		
1AX									<2 438		<8'			
1BBB	9 125	0 -10	29' 11 1/4''		2 438	0 -5	8	0 -3/16	2 896 ^b	0 -5	9' 6'' ^b	0 -3/16	30 480 ^a	67 200 ^a
1BB									2 591 ^b	0 -5	8' 6'' ^b	0 -3/16		
1B									2 438	0 -5	8'	0 -3/16		
1BX									<2 438		<8'			
1CCC	6 058	0 -6	19' 10 1/2''	0 -1/4	2 438	0 -5	8	0 -3/16	2 896 ^b	0 -5	9' 6''	0 -3/16	30 480 ^a	67 200 ^a
1CC									2 591 ^b	0 -5	8' 6'' ^b	0 -3/16		
1C									2 438	0 -5	8'	0 -3/16		
1CX									<2 438		<8'			

^a Higher values are permissible under certain conditions. See 5.2.2.

^b Legal limitations to the overall height of vehicle and load can exist in certain countries (for example for rail/road service).

Table 2 (continued)

Freight container designation	Length, <i>L</i>				Width, <i>W</i>				Height, <i>H</i>			Rating, <i>R</i> ^a (gross mass)		
	tol.		tol.		tol.		tol.		tol.	tol.		kg	lb	
	mm	ft and in	in	mm	ft	in	mm	ft and in	in					
1D	2 991	0 -6	9' 9 3/4"	0 -3/16	2 438	0 -5	8	0 -3/16	2 438	0 -5	8'	0 -3/16	10 160	22 400
1DX									<2 438		<8'			

^a Higher values are permissible under certain conditions. See 5.2.2.

^b Legal limitations to the overall height of vehicle and load can exist in certain countries (for example for rail/road service).

NOTE It can be difficult to provide a 1CCC container with a gooseneck tunnel. 1CCC containers without gooseneck tunnels can meet height problems in some countries while circulating on the road on straight frame container chassis.

Table 3 — Minimum internal dimensions and door opening dimensions for series 1 freight containers

Dimensions in millimetres

Freight container designation	Minimum internal dimensions			Minimum door opening dimensions	
	Height	Width	Length	Height	Width
1EEE	Nominal container external height minus 241 mm	2 330	13 542	2 566	2 286
1EE				2 261	
1AAA			11 998	2 566	
1AA			11 998	2 261	
1A			11 998	2 134	
1BBB			8 931	2 566	
1BB			8 931	2 261	
1B			8 931	2 134	
1CCC			5 867	2 566	
1CC			5 867	2 261	
1C			5 867	2 134	
1D			2 802	2 134	