


SVENSK STANDARD

SS-ISO 24043:2020

Marine structures – Crude oil offloading systems – Hose reels  
(ISO 24043:2020, IDT)



**sis** Svenska  
Institutet för  
Standarder

Language: engelska/English

Edition: 1

This preview is downloaded from [www.sis.se](http://www.sis.se). Buy the entire standard via <https://www.sis.se/std-80025767>

Den här standarden kan hjälpa dig att effektivisera och kvalitetssäkra ditt arbete. SIS har fler tjänster att erbjuda dig för att underlätta tillämpningen av standarder i din verksamhet.

#### **SIS Abonnemang**

Snabb och enkel åtkomst till gällande standard med SIS Abonnemang, en prenumerationstjänst genom vilken din organisation får tillgång till all världens standarder, senaste uppdateringarna och där hela din organisation kan ta del av innehållet i prenumerationen.

#### **Utbildning, event och publikationer**

Vi erbjuder även utbildningar, rådgivning och event kring våra mest sålda standarder och frågor kopplade till utveckling av standarder. Vi ger också ut handböcker som underlättar ditt arbete med att använda en specifik standard.

#### **Vill du delta i ett standardiseringsprojekt?**

Genom att delta som expert i någon av SIS 300 tekniska kommittéer inom CEN (europeisk standardisering) och/eller ISO (internationell standardisering) har du möjlighet att påverka standardiseringsarbetet i frågor som är viktiga för din organisation. Välkommen att kontakta SIS för att få veta mer!

#### **Kontakt**

Skriv till [kundservice@sis.se](mailto:kundservice@sis.se), besök [sis.se](https://www.sis.se) eller ring 08 - 555 523 10

---

© Copyright/Upphovsrätten till denna produkt tillhör Svenska institutet för standarder, Stockholm, Sverige. Upphovsrätten och användningen av denna produkt regleras i slutanvändarlicensen som återfinns på [sis.se/slutanvandarlicens](https://www.sis.se/slutanvandarlicens) och som du automatiskt blir bunden av när du använder produkten. För ordlista och förkortningar se [sis.se/ordlista](https://www.sis.se/ordlista).

© Copyright Svenska institutet för standarder, Stockholm, Sweden. All rights reserved. The copyright and use of this product is governed by the end-user licence agreement which you automatically will be bound to when using the product. You will find the licence at [sis.se/enduserlicenseagreement](https://www.sis.se/enduserlicenseagreement).

Upplysningar om sakinnehållet i standarden lämnas av Svenska institutet för standarder, telefon 08 - 555 520 00. Standarder kan beställas hos SIS som även lämnar allmänna upplysningar om svensk och utländsk standard.

Standarden är framtagen av kommittén för Lastsäkring - Godstransporter, SIS/TK 591.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på [www.sis.se](https://www.sis.se) - där hittar du mer information.

Den internationella standarden ISO 24043:2020 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 24043:2020.

The International Standard ISO 24043:2020 has the status of a Swedish Standard. This document contains the official English version of ISO 24043:2020.

# Contents

Page

<b>Foreword</b> .....	<b>v</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Types</b> .....	<b>2</b>
4.1 Basic functions.....	2
4.2 Material stress.....	2
4.3 Design and structure.....	2
4.3.1 General requirement .....	2
4.3.2 Drum design.....	2
4.3.3 Through-flow unit.....	3
4.3.4 Frame design.....	3
4.3.5 Drive unit .....	3
4.3.6 Brake device .....	3
4.3.7 Emergency release equipment.....	4
4.3.8 Operating device.....	4
4.3.9 Auxiliary equipment.....	4
<b>5 Acceptance tests</b> .....	<b>4</b>
5.1 General requirement.....	4
5.2 No-load test.....	4
5.3 Load test .....	5
5.4 Braking test .....	5
5.5 Pressure test .....	5
<b>6 Designation system</b> .....	<b>5</b>
6.1 Designation of product models.....	5
6.2 Nameplate.....	6

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see [www.iso.org/directives](http://www.iso.org/directives)).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Technical Committee ISO/TC 8, *Ships and marine technology*, Subcommittee SC 4, *Outfitting and deck machinery*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at [www.iso.org/members.html](http://www.iso.org/members.html).



# Marine structures — Crude oil offloading systems — Hose reels

## 1 Scope

This document specifies requirements for the design, operation and acceptance tests of hose reels for crude oil offloading systems.

It is applicable to the design, manufacture and acceptance of hose reels for crude oil offloading systems used on marine structures such as floating production storage & offloading (FPSO) and mobile platforms.

## 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3828, *Shipbuilding and marine structures — Deck machinery — Vocabulary and symbols*

## 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 3828 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

### 3.1

#### **rated load**

maximum pulling force of the hose that the drum can withstand when the drum is wound at a *rated speed* (3.4) with a single layer of hose wrapped around

### 3.2

#### **maximum sustained load**

maximum pull of the first layer of hose that the drum can withstand when the reel is in a braking state

### 3.3

#### **emergency release load**

pull acted on the hose upon the release of the emergency rescue device, which is installed to prevent the drum from breaking due to excessive hose pull in the offloading process

### 3.4

#### **rated speed**

maximum retrieval speed that the reel can maintain when the hose reel is subjected to the *rated load* (3.1)

### 3.5

#### **working pressure**

maximum working pressure of crude oil medium in the hose reel's piping

### 3.6

#### **reel capacity**

capacity of the hose reel drum to store the offloading hose, indicating the total length of the offloading hose with a certain outside diameter it can store

## 4 Types

### 4.1 Basic functions

Hose reels shall have (but not be limited to) the following basic functions:

- 1) The reel shall have the capacity to store, retrieve and launch the hose.
- 2) The reel shall allow the flow of fluid medium with certain pressure during the offloading operation.
- 3) In case of emergency, the hose reel shall have the capacity to release the offloading hose and emergency shutdown of the flow pipe.

### 4.2 Material stress

**4.2.1** When the hose reel is droved by the drive unit with the rated load to calculate the stress of transmission and other affected parts, the stress shall not exceed 66 % of the yield limit of the material.

**4.2.2** When the reel is under the maximum sustained load, the stress of the affected parts shall not exceed 90 % of the yield limit of the material.

### 4.3 Design and structure

#### 4.3.1 General requirement

The hose reel is mainly composed of a drum, a through-flow unit, frames, drive units, a brake device, an emergency release device, operating devices and auxiliary equipment.

#### 4.3.2 Drum design

**4.3.2.1** The minimum bottom diameter,  $D$ , of the drum (see [Figure 1](#)) shall not be less than 2 times the minimum bending radius of the selected offloading hose.

**4.3.2.2** The size of the drum shall be such that the offloading hose is fully stored. The outer surface of the drum shall not have sharp edges or other protruding structures that can squeeze or damage the outer surface of the hose.

**4.3.2.3** The crane neck structure connected with the first section of the offloading hose protruding from the surface of the cylinder barrel shall be provided with a safety guardrail around it to guide the hose retrieval to avoid hose damages as described in [4.3.2.2](#).

**4.3.2.4** The reel shall be designed to store the hose in no more than two layers. When the number of layers wound is one, the last section hoses shall not be squeezed with the flange structure (see [4.3.2.5](#)).