

SVENSK STANDARD

SS-ISO 76:2017



Fastställt/Approved: 2017-12-08
Publicerad/Published: 2017-12-08
Utgåva/Edition: 1
Språk/Language: engelska/English
ICS: 21.100.20

**Rullningslager – Statiska bärighetstal (Revision ISO 76:1987)
(ISO 76:2006, IDT)**

**Rolling bearings – Static load ratings (Revision ISO 76:1987)
(ISO 76:2006, IDT)**

This preview is downloaded from www.sis.se. Buy the entire standard via <https://www.sis.se/std-8030002>

Standarder får världen att fungera

SIS (Swedish Standards Institute) är en fristående ideell förening med medlemmar från både privat och offentlig sektor. Vi är en del av det europeiska och globala nätverk som utarbetar internationella standarder. Standarder är dokumenterad kunskap utvecklad av framstående aktörer inom industri, näringsliv och samhälle och befrämjar handel över gränser, bidrar till att processer och produkter blir säkrare samt effektiviserar din verksamhet.

Delta och påverka

Som medlem i SIS har du möjlighet att påverka framtida standarder inom ditt område på nationell, europeisk och global nivå. Du får samtidigt tillgång till tidig information om utvecklingen inom din bransch.



Ta del av det färdiga arbetet

Vi erbjuder våra kunder allt som rör standarder och deras tillämpning. Hos oss kan du köpa alla publikationer du behöver – allt från enskilda standarder, tekniska rapporter och standardpaket till handböcker och onlinetjänster. Genom vår webbtjänst e-nav får du tillgång till ett lättnavigerat bibliotek där alla standarder som är aktuella för ditt företag finns tillgängliga. Standarder och handböcker är källor till kunskap. Vi säljer dem.

Utveckla din kompetens och lyckas bättre i ditt arbete

Hos SIS kan du gå öppna eller företagsinterna utbildningar kring innehåll och tillämpning av standarder. Genom vår närhet till den internationella utvecklingen och ISO får du rätt kunskap i rätt tid, direkt från källan. Med vår kunskap om standarders möjligheter hjälper vi våra kunder att skapa verklig nytta och lönsamhet i sina verksamheter.

Vill du veta mer om SIS eller hur standarder kan effektivisera din verksamhet är du välkommen in på www.sis.se eller ta kontakt med oss på tel 08-555 523 00.



Standards make the world go round

SIS (Swedish Standards Institute) is an independent non-profit organisation with members from both the private and public sectors. We are part of the European and global network that draws up international standards. Standards consist of documented knowledge developed by prominent actors within the industry, business world and society. They promote cross-border trade, they help to make processes and products safer and they streamline your organisation.

Take part and have influence

As a member of SIS you will have the possibility to participate in standardization activities on national, European and global level. The membership in SIS will give you the opportunity to influence future standards and gain access to early stage information about developments within your field.

Get to know the finished work

We offer our customers everything in connection with standards and their application. You can purchase all the publications you need from us - everything from individual standards, technical reports and standard packages through to manuals and online services. Our web service e-nav gives you access to an easy-to-navigate library where all standards that are relevant to your company are available. Standards and manuals are sources of knowledge. We sell them.

Increase understanding and improve perception

With SIS you can undergo either shared or in-house training in the content and application of standards. Thanks to our proximity to international development and ISO you receive the right knowledge at the right time, direct from the source. With our knowledge about the potential of standards, we assist our customers in creating tangible benefit and profitability in their organisations.

If you want to know more about SIS, or how standards can streamline your organisation, please visit www.sis.se or contact us on phone +46 (0)8-555 523 00



Den internationella standarden ISO 76:2006 gäller som svensk standard. Detta dokument innehåller den officiella engelska versionen av ISO 76:2006.

The International Standard ISO 76:2006 has the status of a Swedish Standard. This document contains the official version of ISO 76:2006.

© Copyright/Upphovsrätten till denna produkt tillhör SIS, Swedish Standards Institute, Stockholm, Sverige. Användningen av denna produkt regleras av slutanvändarlicensen som återfinns i denna produkt, se standardens sista sidor.

© Copyright SIS, Swedish Standards Institute, Stockholm, Sweden. All rights reserved. The use of this product is governed by the end-user licence for this product. You will find the licence in the end of this document.

Upplysningar om sakinnehållet i standarden lämnas av SIS, Swedish Standards Institute, telefon 08-555 520 00. Standarder kan beställas hos SIS Förlag AB som även lämnar allmänna upplysningar om svensk och utländsk standard.

Information about the content of the standard is available from the Swedish Standards Institute (SIS), telephone +46 8 555 520 00. Standards may be ordered from SIS Förlag AB, who can also provide general information about Swedish and foreign standards.

Denna standard är framtagen av kommittén för Rullningslager, SIS/TK 105.

Har du synpunkter på innehållet i den här standarden, vill du delta i ett kommande revideringsarbete eller vara med och ta fram andra standarder inom området? Gå in på www.sis.se - där hittar du mer information.

Contents

Page

Foreword.....	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions.....	1
4 Symbols	3
5 Radial ball bearings	4
5.1 Basic static radial load rating	4
5.2 Static equivalent radial load	6
6 Thrust ball bearings.....	7
6.1 Basic static axial load rating	7
6.2 Static equivalent axial load	7
7 Radial roller bearings	7
7.1 Basic static radial load rating.....	7
7.2 Static equivalent radial load	8
8 Thrust roller bearings.....	9
8.1 Basic static axial load rating	9
8.2 Static equivalent axial load.....	9
9 Static safety factor.....	10
9.1 General.....	10
9.2 Ball bearings	10
9.3 Roller bearings.....	11
Annex A (informative) Discontinuities in the calculation of basic static load ratings	12

SS-ISO 76:2017 (E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 76 was prepared by Technical Committee ISO/TC 4, *Rolling bearings*, Subcommittee SC 8, *Load ratings and life*.

This third edition cancels and replaces the second edition (ISO 76:1987), which has been technically revised. It incorporates ISO 76:1987/Amd 1:1999 in Annex A.

Introduction

Permanent deformations appear in rolling elements and raceways of rolling bearings under static loads of moderate magnitude and increase gradually with increasing load.

It is often impractical to establish whether the deformations appearing in a bearing in a specific application are permissible by testing the bearing in that application. Other methods are therefore required to establish the suitability of the bearing selected.

Experience shows that a total permanent deformation of 0,000 1 of the rolling element diameter, at the centre of the most heavily loaded rolling element/raceway contact, can be tolerated in most bearing applications without the subsequent bearing operation being impaired. The basic static load rating is, therefore, given a magnitude such that, approximately, this deformation occurs when the static equivalent load is equal to the load rating.

Tests in different countries indicate that a load of the magnitude in question can be considered to correspond to a calculated contact stress of

- 4 600 MPa¹⁾ for self-aligning ball bearings,
- 4 200 MPa for all other ball bearings, and
- 4 000 MPa for all roller bearings,

at the centre of the most heavily loaded rolling element/raceway contact. The equations and factors for the calculation of the basic static load ratings are based on these contact stresses.

The permissible static equivalent load could be smaller than, equal to or greater than the basic static load rating, depending on the requirements for smoothness of operation and friction, as well as on actual contact surface geometry. Bearing users without previous experience of these conditions will need to consult the bearing manufacturer.

1) 1 bar = 0,1 MPa = 10⁵ Pa; 1 MPa = 1 N/mm²

Rolling bearings — Static load ratings

1 Scope

This International Standard specifies methods of calculating the basic static load rating and the static equivalent load for rolling bearings within the size ranges shown in the relevant ISO standards, manufactured from contemporary, commonly used, high quality, hardened bearing steel in accordance with good manufacturing practice and basically of conventional design as regards the shape of the rolling contact surfaces.

Calculations carried out in accordance with this International Standard do not yield satisfactory results for bearings in which, because of application conditions and/or internal design, there is a considerable truncation of the area of contact between the rolling elements and the ring raceways. The same limitation applies where application conditions cause deviations from a normal load distribution in the bearing, for example misalignment, preload or extra large clearance or where special surface treatment or coatings are used. Where there is reason to assume that such conditions prevail, the user should consult the bearing manufacturer for recommendations and the evaluation of the static equivalent load.

This International Standard is not applicable to designs where the rolling elements operate directly on a shaft or housing surface, unless that surface is equivalent in all respects to the bearing surface it replaces.

Double-row radial bearings and double-direction thrust bearings are, when referred to in this International Standard, presumed to be symmetrical.

In addition, guidelines are given for static safety factors to be applied in heavy loaded applications.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 5593, *Rolling bearings — Vocabulary*

ISO 15241, *Rolling bearings — Symbols for quantities*

ISO/TR 10657:1991, *Explanatory notes on ISO 76*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 5593 and the following apply.

3.1

static load

load acting on a bearing when the speed of rotation of its rings or washers in relation to each other is zero

SS-ISO 76:2017 (E)

3.2
basic static radial load rating
radial load which corresponds to a calculated contact stress at the centre of the most heavily loaded rolling element/raceway contact of

- 4 600 MPa for self-aligning ball bearings,
- 4 200 MPa for all other radial ball bearings types, and
- 4 000 MPa for all radial roller bearings

NOTE 1 In the case of a single-row angular contact bearing, the radial load rating refers to the radial component of that load which causes a purely radial displacement of the bearing rings in relation to each other.

NOTE 2 For these contact stresses, under static load, a total permanent deformation of rolling element and raceway occurs which is approximately 0,000 1 of the rolling element diameter.

3.3
basic static axial load rating
static centric axial load which corresponds to a calculated contact stress at the centre of the most heavily loaded rolling element/raceway contact of

- 4 200 MPa for thrust ball bearings, and
- 4 000 MPa for all thrust roller bearings

NOTE For these contact stresses, under static load, a total permanent deformation of rolling element and raceway occurs which is approximately 0,000 1 of the rolling element diameter.

3.4
static equivalent radial load
static radial load which would cause the same contact stress at the centre of the most heavily loaded rolling element/raceway contact as that which occurs under the actual load conditions

3.5
static equivalent axial load
static centric axial load which would cause the same contact stress at the centre of the most heavily loaded rolling element/raceway contact as that which occurs under the actual load conditions

3.6
static safety factor
ratio between the basic static load rating and the static equivalent load, giving a margin of safety against inadmissible permanent deformation on rolling elements and raceways

3.7
roller diameter
<calculation of load ratings> theoretical diameter in a radial plane through the middle of the roller length for a symmetrical roller

NOTE 1 For a tapered roller, the applicable diameter is equal to the mean value of the diameters at the imaginary sharp corners at the large end and at the small end of the roller.

NOTE 2 For an asymmetrical convex roller, the applicable diameter is an approximation of the diameter at the point of contact between the roller and the ribless raceway at zero load.

3.8
effective roller length
<calculation of load ratings> theoretical maximum length of contact between a roller and that raceway where the contact is shortest

NOTE This is normally taken to be either the distance between the theoretically sharp corners of the roller minus the roller chamfers, or the raceway width excluding the grinding undercuts, whichever is the smaller.

3.9

nominal contact angle

angle between a plane perpendicular to a bearing axis (a radial plane) and the nominal line of action of the resultant of the forces transmitted by a bearing ring or washer to a rolling element

NOTE For bearings with asymmetrical rollers, the nominal contact angle is determined by the contact with the ribless raceway.

3.10

pitch diameter of ball set

diameter of the circle containing the centres of the balls in one row in a bearing

3.11

pitch diameter of roller set

diameter of the circle intersecting the roller axes at the middle of the rollers in one row in a bearing

4 Symbols

For the purposes of this document, the symbols given in ISO 15241 and the following apply.

C_{0a} basic static axial load rating, in newtons

C_{0r} basic static radial load rating, in newtons

D_{pw} pitch diameter of ball or roller set, in millimetres

D_w nominal ball diameter, in millimetres

D_{we} roller diameter applicable in the calculation of load ratings, in millimetres

F_a bearing axial load (axial component of actual bearing load), in newtons

F_r bearing radial load (radial component of actual bearing load), in newtons

f_0 factor for calculation of basic static load rating

i number of rows of rolling elements

L_{we} effective roller length applicable in the calculation of load ratings, in millimetres

P_{0a} static equivalent axial load, in newtons

P_{0r} static equivalent radial load, in newtons

S_0 static safety factor

X_0 static radial load factor

Y_0 static axial load factor

Z number of rolling elements in a single-row bearing; number of rolling elements per row of a multi-row bearing with the same number of rolling elements per row

α nominal contact angle, in degrees